

SS1095 • 14" Marine Crescent Ice Maker • Marine Series





STAINLESS SOLID (FLUSH TO DOOR)



STAINLESS SOLID (NO FLANGE)

FEATURES & BENEFITS

PERFORMANCE

- Uses less than 3 gallons of water to produce up to 23 lbs of ice per day
- Up to 12 lbs in ice storage capacity
- Crescent ice cube dimensions: $^{1}/_{2}''$ W x $^{3}/_{4}''$ H x $^{1}/_{2}''$ L
- On/Off switch is conveniently located on the grille
- Available in 115 or 220 240 volts

INTERIOR/EXTERIOR

- No drain required
- Zero clearance door swing is field reversible
- Standard travel package includes door latch, ensuring safe-at-sea storage
- Corrosion and UV resistant components provide product longevity in harsh environments

INTEGRATION

- Unit is designed to be built-in or can be freestanding
- Multiple flange options

MODEL DETAILS

Model	Voltage	Door Swing	Finish	Shipping Weight
ULN-SS1095FCS-03A	115	Field Reversible (Flush to Cabinet)	Stainless Solid	66 lbs
ULN-SS1095FCS-20A	220 - 240	Field Reversible (Flush to Cabinet)	Stainless Solid	66 lbs
ULN-SS1095FDS-03A	115	Field Reversible (Flush to Door)	Stainless Solid	66 lbs
ULN-SS1095FDS-20A	220 - 240	Field Reversible (Flush to Door)	Stainless Solid	66 lbs
ULN-SS1095NFS-03A	115	Field Reversible (No Flange)	Stainless Solid	66 lbs
ULN-SS1095NFS-20A	220 - 240	Field Reversible (No Flange)	Stainless Solid	66 lbs


ACCESSORIES

Model	Description	Finish	Shipping Weight
WATERHOOKUP	Braided water supply line kit	na	2 lbs




Marine Series • 14" Marine Crescent Ice Maker • SS1095

DIMENSIONS



CABINET CUT-OUT



INSTALLATION NOTES

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

SPECIFICATIONS

SS1095	
2.5	
1.2	
18	
6	
on/off switch	
Manual	
17" / 432 mm	
25 ½16" / 637 mm	
14" / 356 mm	
17" / 432 mm	
25 ½" / 638 mm	
15 1/8" / 384 mm	
17" / 432 mm	
26 ½16" / 662 mm	
15 ¹⁵ / ₁₆ " / 405 mm	
na	
23 lbs	
12 lbs	
60 lbs	
R134A	
No	

ELECTRICAL REQUIREMENTS

This unit requires a grounded a polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).





UL listing only applies to 115 v models.

Please visit u-line.com to view this model's User Guide. All specifications are subject to change without notice.